

Anti-Slip Hi-Traction®  
**ROLL-TRACTION®**  
Anti-Slip Walkway Cover

**SAFEGUARD**  
TECHNOLOGY  
*Leading Manufacturer of Anti-Slip Safety Products*



## Cost Effective and Portable Solution for Slips-and-Falls over large areas.

SAFEGUARD® Roll-Traction® Walkway Covers are a durable, pliable, and portable solution for eliminating slips and falls on wet, oily, and slippery surfaces.



[www.safeguard-technology.com](http://www.safeguard-technology.com)

Step Covers | Walkway Covers | Ladder Rung Covers | Pipe & Cable Covers | Roll-Traction® | Anti-Slip Mats | Anti-Slip Tapes

# Anti-Slip Hi-Traction® ROLL-TRACTION® Anti-Slip Walkway Cover

**SAFEGUARD® Roll-Traction®**  
Heavy-duty movable Walkway Cover  
for large areas.



SAFEGUARD® Roll-Traction® Walkway Covers offer excellent protection against slips and falls.

Water, oils, and chemicals can create dangerous working surfaces when introduced on walkways, decks, and floors. By using SAFEGUARD® Roll-Traction® Anti-Slip Walkway Covers, a secure, anti-slip area can quickly and conveniently be created any where. This heavy duty, flexible polymeric geomembrane can be put down temporarily for easy removal and cleaning. Roll-Traction® can also be secured by mechanical fasteners or adhesives for a more permanent installation.

### Grit and thickness to suit your application

Roll-Traction®		Average Thickness Inches	Average Thickness Millimeters
Grade	Coarse	0.101"	2.6mm
	Fine	0.095"	2.4mm
	Extra Fine	0.087"	2.2mm
	Super Fine	0.080"	2.0mm

*Average Weight: 0.8lb / Sq. foot (0.36kg. / Sq. meter) with Coarse grade grit*

### Maximum Available Sizes

Roll-Traction®	
Width	Length
29" Width	40' Max Length
(.75m) 736.6mm Width	12m Max Length
40" Width	30' Max Length
(1m) 1016mm Width	9m Max Length
58" Width	20' Max Length
(1.5m) 1473.2mm Width	6m Max Length

*\*Custom widths are available in combined lengths over 126' or 38.4m*  
*\*\*Super Coarse/Xtreme and Extra Coarse are not available on Roll-Traction®*



- Prevents slips and falls
- Impact & puncture resistant
- Easily installed
- Non-conductive
- High strength
- Corrosion resistant
- Can be rolled for storage
- Meets OSHA & ADA Coefficient of Friction Guidelines

**Superior Coefficient of Friction**  
SAFEGUARD® Technology's Hi-Traction® surface nearly doubles both OSHA 0.5 and ADA 0.6 guidelines for Coefficient of Friction values<sup>1</sup>, even in wet or oily conditions.

<sup>1</sup>Confirmed in independent lab testing using the Mark II Model of the Brungraber slip tester.

### Grit Sizes and Color

Choose from four grades of grit (not available in Super Coarse/Xtreme or Extra Coarse/Offshore) and standard colors only. Due to the length of the rolls, two-tone color configurations are only available at the ends, across the width of the Cover. Glow Colors can be done in two-tone configurations and are only on the ends of the Roll-Traction®.

Contact Safeguard Technology for more information or a free sample today.



**SAFEGUARD TECHNOLOGY INC.**  
330.995.5200 | 1.800.989.1695 Toll-Free in the U.S. and Canada  
Email: info@safeguard-technology.com  
www.safeguard-technology.com

© Copyright 2016 SAFEGUARD TECHNOLOGY INC.  
SAFEGUARD® Covers, Hi-Traction®, HiGlo-Traction®, and Roll-Traction® are registered trademarks of SAFEGUARD Technology Inc. REV2\_122115